


Eliche a tre pale tipo E12




AS/AD 43%
Fa/F 43%

P/D Max 0.7



Ø elica in mm	Ø elica in "	Foro max mm
305	12	25
330	13	25
355	14	25
380	15	25
405	16	30
430	17	30
455	18	30
480	19	35
505	20	35

Eliche a tre pale tipo E13




AS/AD 52%
Fa/F 52%

P/D Max 0.85



Ø elica in mm	Ø elica in "	Foro max mm
305	12	30
330	13	30
355	14	30
380	15	35
405	16	35
430	17	35
455	18	40
480	19	40
505	20	45
535	21	45
560	22	45
585	23	45
610	24	60
635	25	60
660	26	60
685	27	60
710	28	70
735	29	70
760	30	70

Eliche a tre pale tipo C7




AS/AD 55%
Fa/F 55%

P/D Max 1.2



Ø elica in mm	Ø elica in "	Foro max mm
330	13	25
355	14	25
380	15	30
405	16	35
430	17	35
455	18	40
480	19	40
505	20	40
535	21	45
560	22	45
585	23	50
610	24	60
635	25	60
660	26	60

Eliche a tre pale tipo E12



AS/AD 75%
Fa/F 75%

P/D Max 1.5



Ø elica in mm	Ø elica in "	Foro max mm
405	16	40
430	17	40
455	18	40
480	19	50
505	20	50
535	21	50
560	22	50
585	23	50
610	24	50
635	25	60
660	26	60
685	27	60
710	28	60
735	29	70
760	30	70