


Eliche a quattro pale tipo B6




AS/AD 57%
Fa/F 57%

P/D Max 0.7



Ø elica in mm	Ø elica in "	Foro max mm
660	26	60
685	27	60
710	28	60
735	29	70
760	30	70

Eliche a quattro pale tipo B7




AS/AD 69%
Fa/F 69%

P/D Max 0.7



Ø elica in mm	Ø elica in "	Foro max mm
405	16	35
430	17	35
455	18	40
480	19	40
505	20	45
535	21	45
560	22	45
585	23	45
610	24	60
635	25	60
660	26	60
685	27	60
710	28	70
735	29	70
760	30	70

Eliche a quattro pale tipo S8




AS/AD 74%
Fa/F 74%

P/D Max 1.5



Ø elica in mm	Ø elica in "	Foro max mm
430	17	40
455	18	40
480	19	40
505	20	40
535	21	50
560	22	50
585	23	50
610	24	50
635	25	60
660	26	60
685	27	60
710	28	60
735	29	70
760	30	70

Eliche a quattro pale tipo S8m



AS/AD 90%
Fa/F 90%

P/D Max 1.5



Ø elica in mm	Ø elica in "	Foro max mm
430	17	35
455	18	40
480	19	40
505	20	50
535	21	50
560	22	50
585	23	50
610	24	50
635	25	60
660	26	60
685	27	60
710	28	60
735	29	70
760	30	70